


# Orion Alnitak

Indoor Lighting - Surface Mounted Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	Electrostatic coated aluminum profile
<b>Optics</b>	Highly transmissive opal diffuser
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	
<b>Mounting System</b>	Surface
<b>Side Diffuser Color Options</b>	White,Blue,Green,Magenta and Red

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	80
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K

## ELECTRICAL

<b>Power (W)</b>	9-33W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
Emergency Lighting Unit  
Tunable White

## ASSEMBLY

**Installation Type** Surface Mounted

Order Code	W	Lm	CCT	CRI	WxLxH (mm)	
03101.33.30.008	9	800	3000	Ra>80	310x310x120	2,0
03101.33.40.009	9	850	4000	Ra>80	310x310x120	2,0
03101.66.30.032	28	3200	3000	Ra>80	595x595x120	3,8
03101.66.40.033	28	3300	4000	Ra>80	595x595x120	3,8
03101.66.30.036	33	3600	3000	Ra>80	595x595x120	3,8
03101.66.40.039	33	3700	4000	Ra>80	595x595x120	3,8

