



Orion Alnitak

Indoor Lighting - Surface Mounted Lighting



TECHNICAL INFORMATION

Housing	Electrostatic coated aluminum profile
Optics	Highly transmissive opal diffuser
LED Lifetime	50.000 hours
L80B50	
Mounting System	Surface
Side Diffuser Color Options	White,Blue,Green,Magenta and Red

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	80
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	3000K/4000K

ELECTRICAL

Power (W)	9-33W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit
Tunable White

ASSEMBLY

Installation Type Surface Mounted

Order Code	W	Lm	CCT	CRI	WxLxH (mm)	
03101.33.30.008	9	800	3000	Ra>80	310x310x120	2,0
03101.33.40.009	9	850	4000	Ra>80	310x310x120	2,0
03101.66.30.032	28	3200	3000	Ra>80	595x595x120	3,8
03101.66.40.033	28	3300	4000	Ra>80	595x595x120	3,8
03101.66.30.036	33	3600	3000	Ra>80	595x595x120	3,8
03101.66.40.039	33	3700	4000	Ra>80	595x595x120	3,8

