

Dove

Indoor Lighting - Industrial Lighting



TECHNICAL INFORMATION

Housing	Impact resistant PC
Optics	Highly transmissive opal PC diffuser
LED Lifetime	50.000 hours
L80B50	
Mounting System	Surface

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	80
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	3000K/4000K

ELECTRICAL




Power (W)	15-25W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit

ASSEMBLY

Installation Type Surface Mounted



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
06152.34.30.014	15	1500	3000	Ra>80	340x120	1,3
06152.34.40.015	15	1400	4000	Ra>80	340x120	1,3
06152.34.30.017	18	1800	3000	Ra>80	340x120	1,3
06152.34.40.018	18	1700	4000	Ra>80	340x120	1,3
06152.34.30.026	25	2700	3000	Ra>80	340x120	1,3
06152.34.40.027	25	2600	4000	Ra>80	340x120	1,3

