

# Dove

Indoor Lighting - Industrial Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	Impact resistant PC
<b>Optics</b>	Highly transmissive opal PC diffuser
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	
<b>Mounting System</b>	Surface

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	80
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K

## ELECTRICAL




<b>Power (W)</b>	15-25W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
Emergency Lighting Unit

## ASSEMBLY

**Installation Type** Surface Mounted



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
06152.34.30.014	15	1500	3000	Ra>80	340x120	1,3
06152.34.40.015	15	1400	4000	Ra>80	340x120	1,3
06152.34.30.017	18	1800	3000	Ra>80	340x120	1,3
06152.34.40.018	18	1700	4000	Ra>80	340x120	1,3
06152.34.30.026	25	2700	3000	Ra>80	340x120	1,3
06152.34.40.027	25	2600	4000	Ra>80	340x120	1,3

