

Plate

Outdoor Lighting - Outdoor Sconce



Colour Options



Ral 7016

TECHNICAL INFORMATION

Housing	Cast Aluminum
Diffuser	Opal Polycarbonate Diffuser
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	UGR ≤ 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL



Power (W)	14-19W
Power Factor	>0.95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- 2700K ~ 6500K	- CRI > 90
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted



Order Code	W	Light Source	CCT	CRI	ØxH (mm)	Kg
09112.27.30.010	14	1150	3000	Ra>80	275x80	1,3
09112.27.40.011	14	1200	4000	Ra>80	275x80	1,3
09112.27.30.016	19	1550	3000	Ra>80	275x80	1,3
09112.27.40.017	19	1600	4000	Ra>80	275x80	1,3

