

Plate

Outdoor Lighting - Outdoor Sconce



Colour Options



Ral 7016

TECHNICAL INFORMATION

Housing Cast Aluminum
Diffuser Opal Polycarbonate Diffuser
Paint Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Light Distribution Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL



Power (W) 14-19W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI
- Tunable White
- 2700K ~ 6500K
- Different RAL Color Options
- Class-I Protection Class
- 1-10V DIM
- Emergency Lighting Unit
- CRI > 90
- Plug-in Connector
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
09112.27.30.010	14	900	3000	Ra>80	275x80	1,3
09112.27.40.011	14	1000	4000	Ra>80	275x80	1,3
09112.27.30.016	19	1150	3000	Ra>80	275x80	1,3
09112.27.40.017	19	1250	4000	Ra>80	275x80	1,3

