


Escape

Indoor Lighting - Emergency Lighting and Directional Luminaire



Colour Options 
Ral 9016

TECHNICAL INFORMATION

Housing Polycarbonate and Hanger Tie
Frame Foil Printed Acrylic Lens
Diffuser Transparent Plexiglass
Paint Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

ELECTRICAL


Power (W) 1.2W
Power Factor >0.90
Light Source SMD Mid Power LED
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output Rail Drive
Ambient Temperature 0°C / +40°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI - 1-10V DIM
- Tunable White - Emergency Lighting Unit
- CRI > 90 - 2700K ~ 6500K
- Different RAL Color Options - Plug-in Connector
- Class-I Protection Class - PIR Sensor
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Under Plaster, Surface Mounted
Mounting Apparatus Metal Bracket



Order Code	W	Lm	How to use	Battery	WxHxL (mm)	Kg
80511.000.023-IK23	1,2	20	Tek Yüzlü	3H	40x200x264	0,33

