

# Escape

Indoor Lighting - Emergency Lighting and Directional Luminaire



Colour Options



Ral 9016

## TECHNICAL INFORMATION

<b>Housing</b>	Polycarbonate and Hanger Tie
<b>Frame</b>	Foil Printed Acrylic Lens
<b>Diffuser</b>	Transparent Plexiglass
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

## ELECTRICAL

<b>Power (W)</b>	1.2W
<b>Power Factor</b>	>0.90
<b>Light Source</b>	SMD Mid Power LED
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output Rail Drive
<b>Ambient Temperature</b>	0°C / +40°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- PIR Sensor
- AC-DC Supply(MBS)	

## ASSEMBLY

<b>Installation Type</b>	Under Plaster, Surface Mounted
<b>Mounting Apparatus</b>	Metal Bracket



Order Code	W	Lm	How to use	Battery	WxHxL (mm)	Kg
80512.000.011-IK11-I K12	1,2	20	Çift Yüzlü	3H	40x200x264	0,33

