



RUN

80311-80312

Flexible Mounting Emergency Exit Fixture

Run provides clear guidance for safe evacuation during emergencies. Featuring an anodized aluminum housing and a highly visible acrylic directional panel, it ensures that escape routes are easily and quickly identified. Its articulated mounting system adapts to various ceiling angles and installation conditions, allowing the directional panel to be adjusted to the desired position. This flexibility not only simplifies installation but also ensures that the directional signs are positioned for optimal visibility.

Equipped with an internal battery system that keeps it operational during power outages, Run is an ideal solution for safe evacuation scenarios in offices, shopping centers, hospitals, hotels, educational facilities, and public buildings.



General Information		Electrical Info	
Meterial	Aluminium	**Power**	4,87W
Frame	Foil Printed Acrylic Lens	**Power Factor**	>0.90
Optics	Transparent Plexiglass	**Light Source**	SMD Mid Power LED
Paint	Anodizing	**Input Voltage**	220-240V AC / 50-60 Hz
Side Cover	Policarbon	**LED Driver**	Constant Current Output Rail
Insulation Class	Class II	**Ambient Temperature**	0°C / +40°C
Product Dimensions [mm]	40(W)x195/210(H)x265/300(L)		
Mounting Type	Surface and Recessed		
Mounting Part	Metal Bracket		

Lighting Technology
Optional
Emergency Test Button
2700K ~ 6500K
Battery Charge Indicator with Green LED

Order Code	W	How to use	Battery	WxHxL (mm)	Kg
80312.010.003-IK03-IK04	4,87	Çift Yüzlü	3H	40x195x265	0,665

Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/- %10 luk bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K.
Katalogda ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir.
İkizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

+90 (216) 397 22 16
info@ikizleraydinlatma.com