




# Grus Gamma

Indoor Lighting - Pendant Lighting



Order Code	W	Lm	CCT	CRI	L (mm)	Kg
06114.14.30.049	54	4900	3000	Ra>80	255x1435x82	3.0
06114.14.40.051	54	5100	4000	Ra>80	255x1435x82	3.0

## TECHNICAL INFORMATION

<b>Housing</b>	Extruded aluminum profile with electrostatic coating
<b>Optics</b>	Highly transmissive opal diffuser
<b>LED Lifetime L80B50</b>	50.000 hours
<b>Mounting System</b>	Surface / Pendant

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	80
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K

## ELECTRICAL

<b>Power (W)</b>	54W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
Emergency Lighting Unit

## ASSEMBLY

**Installation Type** Pendant

