

U-Line

Indoor Lighting - Pendant Lighting



Colour Options



TECHNICAL INFORMATION

Housing Extruded Aluminum Profile
Diffuser High Transmittance Opal Diffuser
Paint Electrostatic Powder Painted
Dimensions(mm) 95(W) x 75(H)

OPTICAL SPECIFICATIONS

Optics Direct - Indirect
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL

Power (W) 72W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour




OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Different RAL Color Options
- Class-II Protection Class

- 1-10V DIM
- Emergency Lighting Unit
- 2700K ~ 6500K
- Plug-in Energy Input Connector
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Pendant
Mounting Apparatus Height Adjustable Hanging Wire



Order Code	W	Lm	CCT	CRI	L (mm)	Kg
01136.13.30.070	72	7000	3000	Ra>80	1320	2.8
01136.13.40.072	72	7350	4000	Ra>80	1320	2.8

