

Rising

Indoor Lighting - Industrial Lighting



TECHNICAL INFORMATION

Housing	Electrostatic coated steel sheet
Reflector	Anodized aluminum
Glass	Tempered, sand-blasted glass
LED Lifetime	50.000 hours
L80B50	
Mounting System	Surface / Pendant

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	80
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	3000K/4000K

ELECTRICAL




Power (W)	47-200W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free

OPTIONAL

DALI
Emergency Lighting Unit

ASSEMBLY

Installation Type Surface Mounted, Pendant



Order Code	W	Lm	CCT	CRI	WxLxH (mm)	Kg
07301.06.40.056	47	5670	4000	Ra>80	216x633x78	5,8
07301.09.40.085	70	8500	4000	Ra>80	216x915x78	7,0
07301.12.40.113	94	11350	4000	Ra>80	216x1197x78	8,1
07301.15.40.142	120	14200	4000	Ra>80	216x1477x78	9,2
07301.12.40.184	160	18400	4000	Ra>80	291x1197x78	11,5
07301.15.40.225	200	22500	4000	Ra>80	291x1477x78	13,0

