

# Rising

Indoor Lighting - Industrial Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	Electrostatic coated steel sheet
<b>Reflector</b>	Anodized aluminum
<b>Glass</b>	Tempered, sand-blasted glass
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	
<b>Mounting System</b>	Surface / Pendant

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	80
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K

## ELECTRICAL




<b>Power (W)</b>	47-200W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free

## OPTIONAL

DALI  
Emergency Lighting Unit

## ASSEMBLY

**Installation Type** Surface Mounted, Pendant



Order Code	W	Lm	CCT	CRI	WxLxH (mm)	Kg
07301.06.40.056	47	5670	4000	Ra>80	216x633x78	5,8
07301.09.40.085	70	8500	4000	Ra>80	216x915x78	7,0
07301.12.40.113	94	11350	4000	Ra>80	216x1197x78	8,1
07301.15.40.142	120	14200	4000	Ra>80	216x1477x78	9,2
07301.12.40.184	160	18400	4000	Ra>80	291x1197x78	11,5
07301.15.40.225	200	22500	4000	Ra>80	291x1477x78	13,0

