

# Cicala

Indoor Lighting - Emergency Lighting and Directional Luminaire



## Colour Options



Ral 9006

## TECHNICAL INFORMATION

<b>Housing</b>	Metal Sheet
<b>Frame</b>	Metal Sheet
<b>Reflector</b>	Acrylic Lens
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>UGR Value</b>	UGR ≤ 19
<b>CRI</b>	CRI ≥ 80

## ELECTRICAL


<b>Power (W)</b>	1x9-2x9W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	SMD Mid Power LED
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output Rail
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	30.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- PIR Sensor
- AC-DC Supply(MBS)	

## ASSEMBLY

<b>Mounting Apparatus</b>	Metal Bracket
---------------------------	---------------



Order Code	W	Lm	Mode of Operation	Battery	WxHxL (mm)
82210.011.000	2x9	1590	Acil Kesintide	3H	90x200x240

