

# Proof

Indoor Lighting - Industrial Lighting



## TECHNICAL INFORMATION

**Housing** Impact Resistant Gray - PC Injection  
**Diffuser** High Light Transmittance Opal - PC Injection  
**Locking System** Metal Latch - Stainless Steel

## OPTICAL SPECIFICATIONS

**Optics** Symmetrical  
**Light Output Angle** 120°  
**UGR Value** UGR ≤ 22  
**CRI** CRI ≥ 80  
**Color Bin Value** Mc Adams ≤ 3

## ELECTRICAL


**Power (W)** 25-47W  
**Power Factor** >0.95  
**Light Source** SMD Mid Power LED  
**Cabling** Halogen-Free  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Current Output Drive  
**Ambient Temperature** -20°C / +50°C  
**LED Lifetime L80B50** >50.000 Hour

## OPTIONAL

- DALI  
- Tunable White  
- CRI > 90  
- Plug-in Connector  
- PIR Sensor  
- 1-10V DIM  
- Emergency Lighting Unit  
- 2700K ~ 6500K  
- Class-II Protection Class  
- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Surface Mounted  
**Mounting Apparatus** Metal Bracket



Order Code	W	Lm	CCT	Kg	L (mm)
07101.14.30.030	25	2880	3000	1,6	1185
07101.14.40.030	25	3000	4000	1,6	1185
07101.14.30.036	32	3456	3000	1,6	1185
07101.14.40.036	32	3850	4000	1,6	1185
07101.14.30.043	40	4128	3000	1,8	1185
07101.14.40.043	40	4230	4000	1,8	1185
07101.14.30.049	47	4700	3000	1,8	1185
07101.14.40.049	47	4900	4000	1,8	1185
07101.15.40.049	28	3900	4000	2	1485

