


Proof

Indoor Lighting - Industrial Lighting



| Order Code | W | Lm | CCT | Kg | L (mm) |
|-----------------|----|------|------|-----|--------|
| 07101.14.30.043 | 40 | 4128 | 3000 | 1,8 | 1185 |

TECHNICAL INFORMATION

| | |
|-----------------------|--|
| Housing | Impact Resistant Gray - PC Injection |
| Diffuser | High Light Transmittance Opal - PC Injection |
| Locking System | Metal Latch - Stainless Steel |

OPTICAL SPECIFICATIONS

| | |
|---------------------------|--------------|
| Optics | Symmetrical |
| Light Output Angle | 120° |
| UGR Value | UGR ≤ 22 |
| CRI | CRI ≥ 80 |
| Color Bin Value | Mc Adams ≤ 3 |

ELECTRICAL

| | |
|----------------------------|---|
| Power (W) | 25-47W |
| Power Factor | >0.95 |
| Light Source | SMD Mid Power LED |
| Cabling | Halogen-Free |
| Input Voltage | 220-240V AC / 50-60 Hz |
| LED Driver | High Efficiency Constant Current Output Drive |
| Ambient Temperature | -20°C / +50°C |
| LED Lifetime L80B50 | >50.000 Hour |

OPTIONAL

| | |
|---------------------|-----------------------------|
| - DALI | - 1-10V DIM |
| - Tunable White | - Emergency Lighting Unit |
| - CRI > 90 | - 2700K ~ 6500K |
| - Plug-in Connector | - Class-II Protection Class |
| - PIR Sensor | - AC-DC Supply(MBS) |

ASSEMBLY

| | |
|---------------------------|-----------------|
| Installation Type | Surface Mounted |
| Mounting Apparatus | Metal Bracket |

