

Proof

Indoor Lighting - Industrial Lighting




GLOW WIRE
650°C



IK
08



IP
66



Order Code	W	Lm	CCT	Kg	L (mm)
07101.14.40.036	32	3850	4000	1,6	1185

TECHNICAL INFORMATION

Housing Impact Resistant Gray - PC Injection
Diffuser High Light Transmittance Opal - PC Injection
Locking System Metal Latch - Stainless Steel

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL

Power (W) 25-47W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output Drive
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI - 1-10V DIM
- Tunable White - Emergency Lighting Unit
- CRI > 90 - 2700K ~ 6500K
- Plug-in Connector - Class-II Protection Class
- PIR Sensor - AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted
Mounting Apparatus Metal Bracket

