

# Proof

Indoor Lighting - Industrial Lighting





GLOW WIRE  
650°C



IK  
08



IP  
66



Order Code	W	Lm	CCT	Kg	L (mm)
07101.14.40.049	47	4900	4000	1,8	1185

## TECHNICAL INFORMATION

<b>Housing</b>	Impact Resistant Gray - PC Injection
<b>Diffuser</b>	High Light Transmittance Opal - PC Injection
<b>Locking System</b>	Metal Latch - Stainless Steel

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	UGR ≤ 22
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL

<b>Power (W)</b>	25-47W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output Drive
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Plug-in Connector	- Class-II Protection Class
- PIR Sensor	- AC-DC Supply(MBS)

## ASSEMBLY

<b>Installation Type</b>	Surface Mounted
<b>Mounting Apparatus</b>	Metal Bracket

