

Proof

Indoor Lighting - Industrial Lighting




GLOW WIRE
650°C



IK
08



IP
66



Order Code	W	Lm	CCT	Kg	L (mm)
07101.15.40.049	28	3900	4000	2	1485

TECHNICAL INFORMATION

Housing Impact Resistant Gray - PC Injection
Diffuser High Light Transmittance Opal - PC Injection
Locking System Metal Latch - Stainless Steel

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL

Power (W) 25-47W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output Drive
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Plug-in Connector
- PIR Sensor
- 1-10V DIM
- Emergency Lighting Unit
- 2700K ~ 6500K
- Class-II Protection Class
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted
Mounting Apparatus Metal Bracket

