

# Sunny

Outdoor Lighting - Projector



## TECHNICAL INFORMATION

<b>Housing</b>	Electrostatic coated aluminum
<b>Optics</b>	Highly transmissive acrylic optic lens
<b>Glass</b>	Tempered and clear
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	10°-25°-45°-120°
<b>UGR Value</b>	70
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K



## ELECTRICAL

<b>Power (W)</b>	54-151W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

## ASSEMBLY

**Installation Type** Surface Mounted



Order Code	W	Lm	Lm	CRI	WxLxH (mm)	Kg
09290.24.40.061	50	5750	4000	Ra>70	192x377x122	4,8
09290.24.40.077	75	8625	4000	Ra>70	192x377x122	4,8
09290.34.40.111	100	11500	4000	Ra>70	292x377x122	5,8
09290.44.40.162	150	17250	4000	Ra>70	392x377x122	9,3

