

Sunny

Outdoor Lighting - Projector



TECHNICAL INFORMATION

| | |
|---------------------|--|
| Housing | Electrostatic coated aluminum |
| Optics | Highly transmissive acrylic optic lens |
| Glass | Tempered and clear |
| LED Lifetime | 50.000 hours |
| L80B50 | |

OPTICAL SPECIFICATIONS

| | |
|--------------------------------|------------------|
| Light Distribution | Symmetrical |
| Light Output Angle | 10°-25°-45°-120° |
| UGR Value | 70 |
| Color Bin Value | Mc Adams < 3 |
| Color Temperature (CCT) | 3000K/4000K |



ELECTRICAL

| | |
|----------------------|---------------------|
| Power (W) | 54-151W |
| Power Factor | >95 |
| Light Source | SMD Mid Power LED |
| Cabling | Halogen-Free |
| Input Voltage | 220-240V / 50-60 Hz |

OPTIONAL

ASSEMBLY

Installation Type Surface Mounted



| Order Code | W | Lm | Lm | CRI | WxLxH (mm) | Kg |
|-----------------|-----|-------|------|-------|-------------|-----|
| 09290.24.40.061 | 50 | 5750 | 4000 | Ra>70 | 192x377x122 | 4,8 |
| 09290.24.40.077 | 75 | 8625 | 4000 | Ra>70 | 192x377x122 | 4,8 |
| 09290.34.40.111 | 100 | 11500 | 4000 | Ra>70 | 292x377x122 | 5,8 |
| 09290.44.40.162 | 150 | 17250 | 4000 | Ra>70 | 392x377x122 | 9,3 |

