

# Rolling

Indoor Lighting - Recessed Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	Aluminum profile with electrostatic coating
<b>Diffuser</b>	Highly transmissive opal diffuser
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	
<b>Mounting System</b>	Recessed

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Directional
<b>UGR Value</b>	80
<b>Effectiveness Factor</b>	106 Lm/W
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	3000K/4000K

## ELECTRICAL



<b>Power (W)</b>	23-41W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
Emergency Lighting Unit  
Tunable White

## ASSEMBLY

**Installation Type** Under Plaster



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
03170.38.30.023	23	2075	3000	Ra>80	380x82	370	4,6
03170.38.40.024	23	2185	4000	Ra>80	380x82	370	4,6
03170.60.30.042	41	3700	3000	Ra>80	600x82	590	7,2
03170.60.40.043	41	3900	4000	Ra>80	600x82	590	7,2

