

# Beam T

Outdoor Lighting - Outdoor Sconce



## TECHNICAL INFORMATION

<b>Housing</b>	Cast Aluminum
<b>Reflector</b>	Polished Aluminum
<b>Glass</b>	Tempered, Clear Glass Diffuser
<b>Paint</b>	RAL 7016 Anthracite

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Direct
<b>Light Output Angle</b>	43°
<b>UGR Value</b>	UGR ≤ 25
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL



<b>Power (W)</b>	12W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halogen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- 2700K ~ 6500K	- CRI > 90
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Surface Mounted



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
05260.90.30.011	12	1100	3000	Ra>80	90x138	0,65
05260.90.50.012	12	1200	4000	Ra>80	90x138	0,65

