

Beam T

Outdoor Lighting - Outdoor Sconce



TECHNICAL INFORMATION

Housing	Cast Aluminum
Reflector	Polished Aluminum
Glass	Tempered, Clear Glass Diffuser
Paint	RAL 7016 Anthracite

OPTICAL SPECIFICATIONS

Light Distribution	Direct
Light Output Angle	43°
UGR Value	UGR ≤ 25
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL



Power (W)	12W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halogen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- 2700K ~ 6500K	- CRI > 90
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
05260.90.30.011	12	1100	3000	Ra>80	90x138	0,65

