




## MINO



## 05112

### Glass Protected Spot Lighting Fixture

The MINO Series is a professional spotlight solution offering high visual comfort thanks to its internally located optical structure, metallized reflector, and glass-protected system. With a glare value of  $UGR \leq 16$ , it reduces direct visibility of the light source, providing comfortable and controlled lighting.

The aluminum injection-molded body and frame structure give the product high durability and a long lifespan, while its simple design blends seamlessly with modern architectural projects. Its optical structure provides effective results in accent and general lighting applications.

Developed for use in offices, shops, hotels, educational buildings, and commercial spaces, the MINO Series offers an ideal solution for architectural projects with its aesthetic appearance, low glare, and high performance.



| General Information            |                            | Electrical Info            |                        | Lighting Technology                                                     |              |
|--------------------------------|----------------------------|----------------------------|------------------------|-------------------------------------------------------------------------|--------------|
| <b>Body &amp; Frame</b>        | Aluminum Injection         | <b>Power</b>               | 6W-20W                 | <b>Light Output Angle</b>                                               | 32°          |
| <b>Optics</b>                  | Glass + Lens + Reflector   | <b>Power Factor</b>        | >0.95                  | <b>UGR Value</b>                                                        | UGR ≤ 16     |
| <b>Paint</b>                   | Electrostatic Powder Paint | <b>Light Source</b>        | COB LED                | <b>CRI [Ra]</b>                                                         | CRI ≥ 80     |
| <b>Insulation Class</b>        | Class II                   | <b>Cabling</b>             | Halojen-Free           | <b>Color Bin Value</b>                                                  | Mc Adams ≤ 3 |
| <b>Product Dimensions [mm]</b> | Ø60/Ø82/Ø100x66/84/110(H)  | <b>Input Voltage</b>       | 220-240V AC / 50-60 Hz | <b>Optional</b><br>DALI / 1-10V<br>CRI>90 , 2700K~6500K , Tunable White |              |
| <b>Mounting Type</b>           | Recessed                   | <b>LED Driver</b>          | Constant Current       |                                                                         |              |
| <b>Mounting Part</b>           | Steel Spring               | <b>Ambient Temperature</b> | -20°C / +50°C          |                                                                         |              |
|                                |                            | <b>LED Lifetime L70</b>    | >50.000 Hour           |                                                                         |              |

| Order Code      | W  | Lm   | Angle | CCT  | ØD x H (mm) | Ceiling Cutting (mm) | Kg   |
|-----------------|----|------|-------|------|-------------|----------------------|------|
| 05112.10.30.014 | 15 | 1470 | 32°   | 3000 | Ø100x110    | Ø90                  | 0,30 |

