

Minsu

Indoor Lighting - Industrial Lighting



Colour Options



Ral 9006

TECHNICAL INFORMATION

| | |
|-----------------------|---------------------------|
| Housing | Extruded Aluminum Profile |
| Side Cover | PC Injection |
| Diffuser | Opal Diffuser |
| Paint | Anodized Coating |
| Dimensions(mm) | 50(W) x 71(H) |

OPTICAL SPECIFICATIONS

| | |
|---------------------------|--------------|
| Optics | Symmetrical |
| Light Output Angle | 130° |
| UGR Value | UGR ≤ 22 |
| CRI | CRI ≥ 80 |
| Color Bin Value | Mc Adams ≤ 3 |

ELECTRICAL




| | |
|----------------------------|---|
| Power (W) | 11-50W |
| Power Factor | >0.95 |
| Light Source | SMD Mid Power LED |
| Cabling | Halogen-Free |
| Input Voltage | 220-240V AC / 50-60 Hz |
| LED Driver | High Efficiency Constant Current Output |
| Ambient Temperature | -20°C / +50°C |
| LED Lifetime L80B50 | >50.000 Hour |

OPTIONAL

| | |
|-------------------------------|---------------------------|
| - DALI | - 1-10V DIM |
| - Tunable White | - Emergency Lighting Unit |
| - CRI > 90 | - 2700K ~ 6500K |
| - Different RAL Color Options | - Plug-in Connector |
| - Class-II Protection Class | - PIR Sensor |
| - AC-DC Supply(MBS) | |

ASSEMBLY

| | |
|---------------------------|-----------------|
| Installation Type | Surface Mounted |
| Mounting Apparatus | Metal Bracket |



| Order Code | W | Lm | CCT | CRI | WxLxH (mm) | Kg |
|-----------------|----|------|------|-------|------------|-----|
| 07104.11.40.038 | 29 | 3800 | 4000 | Ra>80 | 50x1155x71 | 1.6 |

