




Darkline 1200

Indoor Lighting - Pendant Lighting



Colour Options



Order Code	W	Lm	Angle	CCT	CRI	L (mm)	Kg
02173.31.30.034	31	3800	80°	3000	Ra>80	1200	5,3
02173.31.40.036	31	4000	80°	4000	Ra>80	1200	5,3

TECHNICAL INFORMATION

Housing	Extruded Aluminum Profile
Reflector	Multi Matte Black
Dimensions(mm)	270(W) x 32(H)
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	80°
UGR Value	UGR ≤ 17
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL

Power (W)	31W
Power Factor	>0.95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Connector
- Class-II Protection Class	- AC-DC Supply(MBS)
- Bright / Silver Color Optical Reflector	

ASSEMBLY

Installation Type	Pendant
Mounting Apparatus	Height Adjustable Steel Wire

