

Space IP65

Indoor Lighting - Hidden Lighting



Colour Options



TECHNICAL INFORMATION

Housing Extruded Aluminum Profile
Diffuser Extrusion Diffuser
Paint Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL

Power (W) 7-14W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour




OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Different RAL Color Options
- Class-II Protection Class

- 1-10V DIM
- Emergency Lighting Unit
- 2700K ~ 6500K
- Plug-in Connector
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted
Mounting Apparatus Metal Bracket



Order Code	W/m	Lm	CCT	CRI	WxLxH (mm)	Kg
08131.05.30.007	7	675	3000	Ra>80	21x515x22	0,25
08131.05.40.007	7	725	4000	Ra>80	21x515x22	0,25
08131.10.30.014	14	1350	3000	Ra>80	21x1015x22	0,40
08131.10.40.014	14	1450	4000	Ra>80	21x1015x22	0,40

