

# Escape - Sivaaltı

Indoor Lighting - Emergency Lighting and Directional Luminaire



Colour Options   
Ral 9016

## TECHNICAL INFORMATION

**Housing** Polycarbonate and Hanger Tie  
**Frame** Foil Printed Acrylic Lens  
**Diffuser** Transparent Plexiglass  
**Paint** Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

## ELECTRICAL

**Power (W)** 1.2W  
**Power Factor** >0.90  
**Light Source** SMD Mid Power LED  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Current Output Rail  
**Ambient Temperature** 0°C / +40°C  
**LED Lifetime L80B50** >50.000 Hour

## OPTIONAL

- DALI  
- Tunable White  
- CRI > 90  
- Different RAL Color Options  
- Class-II Protection Class  
- AC-DC Supply(MBS)  
- 1-10V DIM  
- Emergency Lighting Unit  
- 2700K ~ 6500K  
- Plug-in Connector  
- PIR Sensor

## ASSEMBLY

**Installation Type** Under Plaster  
**Mounting Apparatus** Metal Bracket



Order Code	W	Lm	How to use	Battery	WxHxL (mm)	Ceiling Cutting (mm)	Kg
80521.000.014-IK14	1.2	20	Tek Yüzlü	3H	92x210x264	295x50	0,33

