

Apled

Indoor Lighting - Emergency Lighting and Directional Luminaire



Colour Options



Ral 9016

TECHNICAL INFORMATION

Housing	Polycarbonate (PC)
Frame	Foil Printed Acrylic Lens
Diffuser	Transparent Plexiglass
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

UGR Value	UGR ≤ 19
CRI	CRI ≥ 80

ELECTRICAL




Power (W)	3W
Power Factor	>0.95
Light Source	SMD Power LED
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output Rail
Ambient Temperature	-5°C / +40°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Connector
- Class-II Protection Class	- PIR Sensor
- AC-DC Supply(MBS)	

ASSEMBLY

Installation Type	Under Plaster
Mounting Apparatus	Metal Bracket



ÜRÜN YERLEŞİM BİLGİSİ (3W)					
Açık Alan Aydınlatması (min. 0,5 lux için) (Simetrik LENS)			Kaçış Yolu Aydınlatması (min. 1 lux için) (Asimetrik LENS)		
Montaj Yüksekliği (m)	Armatür Duvar Arası Mesafe (m)	Armatür Armatür Arası Mesafe (m)	Montaj Yüksekliği (m)	Armatür Duvar Arası Mesafe (m)	Armatür Armatür Arası Mesafe (m)
2,00	3,00	5,50	2,00	6,50	11,50
2,50	4,00	7,50	2,50	8,00	15,50
3,00	4,50	8,50	3,00	9,50	18,50
3,50	4,50	10,00	3,50	10,50	21,50
4,00	5,00	11,00	4,00	11,00	24,00

Order Code	W	Lm	Mode of Operation	Battery	ØxH (mm)	Kg
------------	---	----	-------------------	---------	----------	----

