

# Sparrow

Indoor Lighting - Spot Lighting



## Colour Options



## TECHNICAL INFORMATION

<b>Housing</b>	Aluminum Injection
<b>Frame</b>	Aluminum Injection
<b>Reflector</b>	Metallized Surface Optics
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	36°-24°-10°
<b>UGR Value</b>	UGR ≤ 22
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL



<b>Power (W)</b>	15-20W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- Tunable White
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	

## ASSEMBLY

**Installation Type** Ray Socket



Order Code	W	Lm	Angle	CCT	CRI	ØxL (mm)	Kg
05668.80.30.017	15	1660	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.018	15	1720	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.021	20	2170	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.022	20	2270	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.014	15	1640	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.015	15	1750	24°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.018	20	1850	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.019	20	1950	24°	4000	Ra>80	Ø60x163x90	1,2



Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/- %10 luk bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K. Katalogta ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir. İkiizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

