

Sparrow

Indoor Lighting - Spot Lighting



Colour Options



TECHNICAL INFORMATION

Housing	Aluminum Injection
Frame	Aluminum Injection
Reflector	Metallized Surface Optics
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	36°-24°-10°
UGR Value	UGR ≤ 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL



Power (W)	15-20W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI
- CRI > 90
- Different RAL Color Options
- Tunable White
- 2700K ~ 6500K

ASSEMBLY

Installation Type Ray Socket



Order Code	W	Lm	Angle	CCT	CRI	ØxL (mm)	Kg
05668.80.30.017	15	1660	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.018	15	1720	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.021	20	2170	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.022	20	2270	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.014	15	1640	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.015	15	1750	24°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.018	20	1850	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.019	20	1950	24°	4000	Ra>80	Ø60x163x90	1,2

