

Star Mini

Indoor Lighting - Spot Lighting



Colour Options



TECHNICAL INFORMATION

Housing	Extruded Aluminum Profile
Frame	Aluminum Injection
Reflector	Optical with Metallized Surface
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	40°, 72°
UGR Value	UGR < 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL



Power (W)	13-38W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	Yüksek Verimli Sabit Akım Çıkışlı
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Energy Input Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type	Under Plaster
Mounting Apparatus	Steel Spring



Order Code	W	Lm	Angle	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
05110.11.30.014	13	1500	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.024	13	1550	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.023	20	2330	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.024	20	2450	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.027	24	2680	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.028	24	2780	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.036	32	3680	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.037	32	3780	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.042	39	4275	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.043	39	4375	40°	4000	Ra>80	Ø119x108	Ø106	0,6



Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/-%10 lük bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K. Katalogta ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir. İkiizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

