

# Star Mini

Indoor Lighting - Spot Lighting



## Colour Options



## TECHNICAL INFORMATION

<b>Housing</b>	Extruded Aluminum Profile
<b>Frame</b>	Aluminum Injection
<b>Reflector</b>	Optical with Metallized Surface
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	40°, 72°
<b>UGR Value</b>	UGR < 22
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL



<b>Power (W)</b>	13-38W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	Yüksek Verimli Sabit Akım Çıkışlı
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Energy Input Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

## ASSEMBLY

<b>Installation Type</b>	Under Plaster
<b>Mounting Apparatus</b>	Steel Spring



Order Code	W	Lm	Angle	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
05110.11.30.014	13	1500	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.024	13	1550	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.023	20	2330	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.024	20	2450	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.027	24	2680	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.028	24	2780	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.036	32	3680	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.037	32	3780	40°	4000	Ra>80	Ø119x108	Ø106	0,6
05110.11.30.042	39	4275	40°	3000	Ra>80	Ø119x108	Ø106	0,6
05110.11.40.043	39	4375	40°	4000	Ra>80	Ø119x108	Ø106	0,6



Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/-%10 lük bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K. Katalogta ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir. İkiizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

Please visit our website for our updated information. [www.ikizleraydinlatma.com](http://www.ikizleraydinlatma.com)

+90 (216) 397 22 16  
info@ikizleraydinlatma.com

