



# Draw

Indoor Lighting - Industrial Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	
<b>Optics</b>	Highly transmissive PC opal diffuser
<b>LED Lifetime</b>	50.000 hours
<b>L80B50</b>	
<b>Mounting System</b>	Surface

## OPTICAL SPECIFICATIONS

<b>Light Distribution</b>	Symmetrical
<b>Light Output Angle</b>	120°
<b>UGR Value</b>	80
<b>Color Bin Value</b>	Mc Adams < 3
<b>Color Temperature (CCT)</b>	4000K

## ELECTRICAL

<b>Power (W)</b>	26-48W
<b>Power Factor</b>	>95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V / 50-60 Hz

## OPTIONAL

DALI  
Emergency Lighting Unit

## ASSEMBLY

Order Code	W	Lm	CCT	CRI	WxLxH (mm)
07102.67.40.030	26	3000	4000	Ra>80	73x1165x79
07102.67.40.041	37	4160	4000	Ra>80	73x1165x79
07102.67.40.049	46	4930	4000	Ra>80	73x1165x79
07102.67.40.038	32	3800	4000	Ra>80	73x1445x79
07102.67.40.045	40	4800	4000	Ra>80	73x1445x79
07102.67.40.052	48	5200	4000	Ra>80	73x1445x79

