



Finger-S

Outdoor Lighting - Urban Lighting



TECHNICAL INFORMATION

Housing Paint Corrosion Resistant Aluminum
Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics Symmetrical / Asymmetrical
Light Output Angle 25°
UGR Value UGR ≤ 25
CRI CRI ≥ 70
Color Bin Value Mc Adams ≤ 3

ELECTRICAL

Power (W) 10W
Power Factor >0.95
Light Source High Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -30°C / +60°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI
- Tunable White
- 2700K ~ 6500K
- Different RAL Color Options
- Class-I Protection Class
- 1-10V DIM
- Emergency Lighting Unit
- CRI > 90
- Plug-in Connector
- AC-DC Supply(MBS)

ASSEMBLY

| Order Code | W | Lm | CCT | CRI | L (mm) |
|-----------------|----|-----|------|-------|--------|
| 09332.16.50.009 | 10 | 800 | 5000 | Ra>70 | 600 |

