

# Panoramic-S

Outdoor Lighting - Urban Lighting



## TECHNICAL INFORMATION

**Housing Paint** Corrosion Resistant Aluminum  
Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

**Optics** Symmetrical  
**Light Output Angle** 25°  
**UGR Value** UGR ≤ 25  
**CRI** CRI ≥ 70  
**Color Bin Value** Mc Adams ≤ 3




## ELECTRICAL

**Power (W)** 40-90W  
**Power Factor** >0.95  
**Light Source** High Power LED  
**Cabling** Halogen-Free  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Current Output  
**Ambient Temperature** -30°C / +60°C  
**LED Lifetime L80B50** >50.000 Hour

## OPTIONAL

- DALI  
- Tunable White  
- 2700K ~ 6500K  
- Different RAL Color Options  
- Class-I Protection Class  
- 1-10V DIM  
- Emergency Lighting Unit  
- CRI > 90  
- Plug-in Connector  
- AC-DC Supply(MBS)

## ASSEMBLY



| Order Code      | W    | Lm    | CCT  | CRI   | L (mm) |
|-----------------|------|-------|------|-------|--------|
| 09492.74.60.150 | 1x90 | 14620 | 6000 | Ra>70 | 6000   |

