



Perla-SK2

Indoor Lighting - Spot Lighting



Colour Options



Order Code	W	Lm	Angle	CCT	CRI	WxLxH (mm)
05480.11.30.020	2X11	2X950	35°	3000	Ra>80	100x200x130
05480.11.40.021	2X11	2X990	35°	4000	Ra>80	100x200x130

TECHNICAL INFORMATION

Housing	Metal Sheet
Frame	Aluminum Injection
Reflector	Metallized Surface Optics
Paint	Electrostatic Powder Coating

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	35°
UGR Value	UGR ≤ 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL

Power (W)	22W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Kit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Class-I Protection Class
- PIR Sensor	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type	Surface Mounted
Mounting Apparatus	Screw Dowel Set

