

Perla-SK2

Indoor Lighting - Spot Lighting



Colour Options



TECHNICAL INFORMATION

| | |
|------------------|------------------------------|
| Housing | Metal Sheet |
| Frame | Aluminum Injection |
| Reflector | Metallized Surface Optics |
| Paint | Electrostatic Powder Coating |

OPTICAL SPECIFICATIONS

| | |
|---------------------------|--------------|
| Optics | Symmetrical |
| Light Output Angle | 35° |
| UGR Value | UGR ≤ 22 |
| CRI | CRI ≥ 80 |
| Color Bin Value | Mc Adams ≤ 3 |

ELECTRICAL



| | |
|----------------------------|---|
| Power (W) | 22W |
| Power Factor | >0.95 |
| Light Source | COB LED |
| Cabling | Halojen-Free |
| Input Voltage | 220-240V AC / 50-60 Hz |
| LED Driver | High Efficiency Constant Current Output |
| Ambient Temperature | -20°C / +50°C |
| LED Lifetime L80B50 | >50.000 Hour |

OPTIONAL

| | |
|-------------------------------|----------------------------|
| - DALI | - 1-10V DIM |
| - Tunable White | - Emergency Lighting Kit |
| - CRI > 90 | - 2700K ~ 6500K |
| - Different RAL Color Options | - Class-I Protection Class |
| - PIR Sensor | - AC-DC Supply(MBS) |

ASSEMBLY

| | |
|---------------------------|-----------------|
| Installation Type | Surface Mounted |
| Mounting Apparatus | Screw Dowel Set |



| Order Code | W | Lm | Angle | CCT | CRI | WxLxH (mm) |
|-----------------|------|-------|-------|------|-------|-------------|
| 05480.11.30.020 | 2X11 | 2X950 | 35° | 3000 | Ra>80 | 100x200x130 |
| 05480.11.40.021 | 2X11 | 2X990 | 35° | 4000 | Ra>80 | 100x200x130 |

