

# Icon

Indoor Lighting - Industrial Lighting



Colour Options



Ral 9016

## TECHNICAL INFORMATION

**Housing** UV Additive PC Injection Molding  
**Diffuser** High Light Transmittance Opal Polycarbonate (PC)

## OPTICAL SPECIFICATIONS

**Optics** Symmetrical  
**Light Output Angle** 120°  
**UGR Value** UGR ≤ 22  
**CRI** CRI ≥ 80  
**Color Bin Value** Mc Adams ≤ 3

## ELECTRICAL



**Power (W)** 13-25W  
**Power Factor** >0.95  
**Light Source** SMD LED  
**Cabling** Halogen-Free  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Current Output  
**Ambient Temperature** -20°C / +50°C  
**LED Lifetime L80B50** >50.000 Hour

## OPTIONAL

- DALI  
- Tunable White  
- CRI > 90  
- Different RAL Color Options  
- PIR Sensor  
- 1-10V DIM  
- Emergency Lighting Unit  
- 2700K ~ 6500K  
- Class-II Protection Class  
- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Surface Mounted  
**Mounting Apparatus** Metal Bracket



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Kg
06152.34.40.017	13	1520	4000	Ra>80	325x100	1,3

