

# Mino 080

Indoor Lighting - Spot Lighting



Colour Options



Ral 9016



Ral 9006



Ral 9005

## TECHNICAL INFORMATION

|           |                                              |
|-----------|----------------------------------------------|
| Housing   | Aluminum Injection                           |
| Frame     | Aluminum Injection                           |
| Reflector | Metallized Surface Optical Reflector + Glass |
| Paint     | Electrostatic Powder Paint                   |

## OPTICAL SPECIFICATIONS

|                    |              |
|--------------------|--------------|
| Optics             | Symmetrical  |
| Light Output Angle | 32°          |
| UGR Value          | UGR ≤ 16     |
| CRI                | CRI ≥ 80     |
| Color Bin Value    | Mc Adams ≤ 3 |

## ELECTRICAL



|                     |                                   |
|---------------------|-----------------------------------|
| Power (W)           | 7-10W                             |
| Power Factor        | >0.95                             |
| Light Source        | COB LED                           |
| Cabling             | Halojen-Free                      |
| Input Voltage       | 220-240V AC / 50-60 Hz            |
| LED Driver          | Yüksek Verimli Sabit Akım Çıkışlı |
| Ambient Temperature | -20°C / +50°C                     |
| LED Lifetime L80B50 | >50.000 Hour                      |

## OPTIONAL

|                               |                                  |
|-------------------------------|----------------------------------|
| - DALI                        | - 1-10V DIM                      |
| - Tunable White               | - Emergency Lighting Unit        |
| - CRI > 90                    | - 2700K ~ 6500K                  |
| - Different RAL Color Options | - Plug-in Energy Input Connector |
| - Class-I Protection Class    | - AC-DC Supply(MBS)              |

## ASSEMBLY

Installation Type Under Plaster



| Order Code      | W | Lm  | Angle | CCT  | CRI   | ØxH (mm) | Cut-out dimensions (mm) | Kg  |
|-----------------|---|-----|-------|------|-------|----------|-------------------------|-----|
| 05112.08.30.006 | 7 | 670 | 32°   | 3000 | Ra>80 | Ø82x84   | Ø75                     | 0,2 |

