

# View

## Indoor Lighting - Recessed Lighting



### Colour Options



Ral 9016

### TECHNICAL INFORMATION

<b>Body &amp; Frame</b>	Sheet Metal
<b>Diffuser</b>	High Transmittance Opal Diffuser
<b>Reflector</b>	Glare Control Optical
<b>Paint</b>	Electrostatic Powder Paint

### OPTICAL SPECIFICATIONS

<b>Optics</b>	Direct-Indirect
<b>Light Output Angle</b>	Indirect 120° Direct 80°
<b>UGR Value</b>	UGR ≤ 17
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

### ELECTRICAL


<b>Power (W)</b>	59W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	SMD Mid Power LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

### OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- PIR Sensor
- AC-DC Supply(MBS)	

### ASSEMBLY

<b>Installation Type</b>	Under Plaster
<b>Mounting Apparatus</b>	Metal Bracket



Order Code	W	Lm	CCT	CRI	WxHxL (mm)	Cut-out dimensions (mm)	Kg
02111.66.30.057	59	4550	3000	Ra>80	595x595x80	575x575	6,5
02111.66.40.057	59	4920	4000	Ra>80	595x595x80	575x575	6,5

