

Rising

Indoor Lighting - Industrial Lighting



Colour Options



TECHNICAL INFORMATION

Housing Metal Sheet
Glass Tempered Clear Glass

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 100°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL



Power (W) 90-120W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +40°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Different RAL Color Options
- Class-II Protection Class
- AC-DC Supply(MBS)
- 1-10V DIM
- Emergency Lighting Unit
- 2700K ~ 6500K
- Plug-in Energy Input Connector
- PIR Sensor

ASSEMBLY

Installation Type Surface Mounted, Pendant
Mounting Apparatus Metal Bracket



Order Code	W	Lm	CCT	Productivity	WxHxL (mm)	Kg
07301.15.40.120	90	12150	4000	133 Lm/W	138x50x920	4
07301.15.65.120	90	11970	6500	133 Lm/W	138x50x920	4
07301.15.40.160	120	16080	4000	133 Lm/W	138x50x1200	5
07301.15.65.160	120	15960	6500	133 Lm/W	138x50x1200	5

