

Altura IP65

Indoor Lighting - Waterproof



Colour Options



Ral 9006

TECHNICAL INFORMATION

Housing CO-EX Extrusion PC Profile
Side Cover PC Injection
Diffuser PC Opal Diffuser

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL



Power (W) 12-44W
Power Factor >0.95
Light Source Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +50°C
LED Lifetime L90B10 >50.000 Hour

OPTIONAL

CRI > 90
Class-II Protection Class
2700K ~ 6500K
Plug-in Energy Input Connector
PIR Sensor

ASSEMBLY

Installation Type Surface Mounted
Mounting Metal Bracket
Apparatus



Order Code	W	Lm	CCT	Productivity	WxHxL (mm)	Kg
07107.06.30.012	12	1320	3000	110 Lm/W	33x50x580	0,4
07107.06.40.013	12	1380	4000	115 Lm/W	33x50x580	0,4
07107.12.30.036	35	3850	3000	110 Lm/W	33x50x1140	0,7
07107.12.40.040	35	4025	4000	115 Lm/W	33x50x1140	0,7
07107.14.30.046	44	4840	3000	110 Lm/W	33x50x1420	1
07107.14.40.050	44	5060	4000	115 Lm/W	33x50x1420	1

