

Deep-Y

Indoor Lighting - Spot Lighting, Surface Mounted Lighting



TECHNICAL INFORMATION

| | |
|------------------|----------------------------|
| Housing | Extruded Aluminum Profile |
| Frame | Aluminum Injection |
| Reflector | Metallized Surface Optical |
| Paint | Electrostatic Powder Paint |

OPTICAL SPECIFICATIONS

| | |
|---------------------------|--------------|
| Optics | Symmetrical |
| Light Output Angle | 36° |
| UGR Value | UGR ≤ 19 |
| CRI | CRI ≥ 80 |
| Color Bin Value | Mc Adams ≤ 3 |

ELECTRICAL



| | |
|----------------------------|---|
| Power (W) | 10W |
| Power Factor | >0.95 |
| Light Source | COB LED |
| Cabling | Halojen-Free |
| Input Voltage | 220-240V AC / 50-60 Hz |
| LED Driver | High Efficiency Constant Current Output |
| Ambient Temperature | -20°C / +50°C |
| LED Lifetime L80B50 | >50.000 Hour |

OPTIONAL

DALI
1-10V DIM
Emergency Lighting Kit
CRI > 90
2700K ~ 6500K
Different RAL Color Options

ASSEMBLY

| | |
|--------------------------|-----------------|
| Installation Type | Surface Mounted |
| Mounting | Screw Dowel Set |
| Apparatus | |



| Order Code | W | Lm | Angle | CCT | CRI | ØxH (mm) | Kg |
|-----------------|----|-----|-------|------|-------|----------|-----|
| 09111.90.40.009 | 10 | 750 | 36° | 4000 | Ra>80 | 80x100 | 0,4 |

