

Deep-K

Indoor Lighting - Spot Lighting, Surface Mounted Lighting



TECHNICAL INFORMATION

Housing	Extruded Aluminum Profile
Frame	Aluminum Injection
Reflector	Metallized Surface Optical
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	36°
UGR Value	UGR ≤ 19
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL


Power (W)	10W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

DALI
1-10V DIM
Emergency Lighting Kit
CRI > 90
2700K ~ 6500K
Different RAL Color Options

ASSEMBLY

Installation Type	Surface Mounted
Mounting	Screw Dowel Set
Apparatus	



Order Code	W	Lm	Angle	CRI	CCT	WxLxH (mm)	Kg
09110.88.40.009	10	750	36°	4000	Ra>80	80x80x100	0,4

