




RAL 9006

DRAX Batwing


07110

Lightweight and Durable Waterproof Lighting

Draw IP65 combines aesthetic appeal with a high level of protection thanks to its slim and compact design. Its CO-EX extruded PC housing offers a lightweight, durable, and corrosion-resistant structure.

The product features an aluminum inner profile where the LED modules and driver are mounted. This structure provides heat management, increasing LED lifespan and supporting mechanical strength. Maintenance and servicing are easily performed thanks to the screw-on side cover system.

It is reliable and long-lasting for corridors, technical areas, parking lots, production areas, warehouses, and humid environments. Its IP65 protection level provides high resistance to dust and moisture.



General Information		Electrical Info		Lighting Technology	
Housing	CO-EX Extrusion PC Profile	Power	21-54W	Light Output Angle	165°x130°
Side Cover	PC Injection + Silicone Gasket	Power Factor	>0.95	UGR Value	UGR ≤ 22
Diffuser	Batwing Acrylic Lens + PC Opal	Light Source	Mid Power LED	CRI [Ra]	CRI ≥ 80
Inner plate	Aluminum Extrusion	Cabling	Halogen-Free	Color Bin Value	Mc Adams ≤ 3
Insulation Class	Class I	Input Voltage	220-240V AC / 50-60 Hz	Optional	
Product Dimensions [mm]	56(W) x 68(H)	LED Driver	Constant Current		DALI / 1-10V
		Ambient Temperature	-20°C / +50°C		CRI>90 , 2700K~6500K , Tunable White
		LED Lifetime L70	>50.000 Hour		Emergency Lighting Unit

Order Code	W	Lm	Angle	CCT	L (mm)	Kg
07110.08.40.031	32	3840	165°-130°	4000	860	0,70

