

# CLEAN ROOM LUMINAIRES





## **LUMINAIRES FOR CLEAN ROOM ENVIRONMENTS**

It is an evident and global fact that health is the most important thing and among all the products, clean room lighting elements are the major players in lighting industry to support healthcare. With the constantly improving technology, clean rooms are used in various areas as pharmaceutical facilities, laboratories, hospitals and food processing. The importance of clean room environments are increasing and the need to build them up precisely tends to rise up, especially with the effect of microelectronics.

## IKIZLER LIGHTING CLEAN ROOM SOLUTIONS

---

Clean rooms are built for many different applications from healthcares to food processing plants; and every field has its own requirements of illuminance. Ikizler offers suitable options for the specific requirements with multiple options of IP - IK ratings, different lumen, UGR, CCT and controlling options. Besides the wide standard range, Ikizler also has the flexibility to customize products almost to a tailor-made point for the needs of the areas to be used. This flexibility also results in a precise integrity of the luminaires with ceiling and other elements of the rooms. Luminaires are in confirmation with the related standards (CE, EMC, RoHS)





# SHIELD

---

## IP65 Clean Room Luminaire

SHIELD Clean Room Luminaire series is used for the majority of clean rooms where the luminaire has to adapt the hygienic needs of environments.



- Direct lighting - wide beam for general illuminance.
- UGR<22 as standard - UGR<19 optional
- Tempered clear glass diffuser for clean room suitability
- Opal diffuser beneath the glass to provide homogenous lighting.
- Electrostatic powder painted durable metal body
- Monobloc poliuretano gasket to provide IP65 rating.
- Chrome plated screws hidden under chrome plated caps to fix the glass.
- Suitable for automation (DALI, 1-10V), human-centric (Tunable) lighting, emergency back-up battery

### Options:

- GST connector
- Security ceiling seismic suspension kit
- Glass security fixation system (to hold glass from one side during installation - maintenance.)
- Various sizes and options to fit different ceilings









# Shield-G 600 Recessed



Standard Colours



|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Diffuser</b>              | Tempered, transparent glass              |
| <b>Optics</b>                | Opal PS diffuser                         |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant current, Pf>0.90                |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |





| Item Code       | W  | Lm   | CCT  | CRI   | WxL     | Installation Dim. (mm) | Kg  |
|-----------------|----|------|------|-------|---------|------------------------|-----|
| 02125.66.30.029 | 28 | 2900 | 3000 | Ra>80 | 595x595 | 580x580                | 7,3 |
| 02125.66.30.032 | 33 | 3200 | 3000 | Ra>80 | 595x595 | 580x580                | 7,3 |
| 02125.66.30.035 | 35 | 3500 | 3000 | Ra>80 | 595x595 | 580x580                | 7,3 |
| 02125.66.40.030 | 28 | 3000 | 4000 | Ra>80 | 595x595 | 580x580                | 7,3 |
| 02125.66.40.032 | 33 | 3300 | 4000 | Ra>80 | 595x595 | 580x580                | 7,3 |
| 02125.66.40.036 | 35 | 3600 | 4000 | Ra>80 | 595x595 | 580x580                | 7,3 |







# Shield-G 1200 Recessed



Standard Colours




|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Diffuser</b>              | Tempered, transparent glass              |
| <b>Optics</b>                | Opal PS diffuser                         |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant current, Pf>0.90                |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |



| Item Code       | W  | Lm   | CCT  | CRI   | WxL      | Installation Dim. (mm) | Kg  |
|-----------------|----|------|------|-------|----------|------------------------|-----|
| 02125.31.30.029 | 33 | 2900 | 3000 | Ra>80 | 295x1195 | 280x1180               | 7,5 |
| 02125.31.30.040 | 52 | 4000 | 3000 | Ra>80 | 295x1195 | 280x1180               | 7,5 |
| 02125.31.40.030 | 33 | 3000 | 4000 | Ra>80 | 295x1195 | 280x1180               | 7,5 |
| 02125.31.40.041 | 52 | 4100 | 4000 | Ra>80 | 295x1195 | 280x1180               | 7,5 |


## Shield-S 600 Surface



Standard Colours



|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Diffuser</b>              | Tempered, transparent glass              |
| <b>Optics</b>                | Opal PS diffuser                         |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant current, Pf>0.90                |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |



| Item Code       | W  | Lm   | CCT  | CRI   | Kg  |
|-----------------|----|------|------|-------|-----|
| 04101.66.30.029 | 28 | 2900 | 3000 | Ra>80 | 7,5 |
| 04101.66.30.033 | 33 | 3200 | 3000 | Ra>80 | 7,5 |
| 04101.66.30.035 | 35 | 3500 | 3000 | Ra>80 | 7,5 |
| 04101.66.40.030 | 28 | 3000 | 4000 | Ra>80 | 7,5 |
| 04101.66.40.032 | 33 | 3300 | 4000 | Ra>80 | 7,5 |
| 04101.66.40.036 | 35 | 3600 | 4000 | Ra>80 | 7,5 |

# WINK

---

## IP65 Clean Room Luminaire

WINK series is used for clean rooms where the luminaire has to adapt the hygienic needs of environments.




### Direct-Indirect lighting

- Tempered clear glass diffuser for clean room suitability
- Opal diffuser beneath the glass to provide homogenous lighting.
- Electrostatic powder painted durable metal body
- Monobloc poliuretano gasket to provide IP65 rating.
- Chrome plated screws hidden under chrome plated caps to fix the glass.
- Suitable for automation (DALI, 1-10V), human-centric (Tunable) lighting, emergency back-up battery

### Options:

- GST connector
- Security ceiling seismic suspension kit
- Glass security fixation system (to hold glass from one side during installation - maintenance.
- Various sizes and options to fit different ceilings


# Wink-G 600 Recessed



Standard Colours



|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Diffuser</b>              | Tempered, transparent glass              |
| <b>Optics</b>                | Opal PS diffuser with indirect louvre    |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant current, Pf>0.90                |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |



| Item Code       | W  | Lm   | CCT  | CRI   | WxL     | Installation Dim. | Kg  |
|-----------------|----|------|------|-------|---------|-------------------|-----|
| 02141.66.30.024 | 32 | 2400 | 3000 | Ra>80 | 595x595 | 580x580           | 6,1 |
| 02141.66.30.047 | 60 | 4700 | 3000 | Ra>80 | 595x595 | 580x580           | 6,1 |
| 02141.66.40.025 | 32 | 2500 | 4000 | Ra>80 | 595x595 | 580x580           | 6,1 |
| 02141.66.40.048 | 60 | 4800 | 4000 | Ra>80 | 595x595 | 580x580           | 6,1 |

# EVEN

---

## IP54 Clean Room Luminaire




- Direct lighting - wide beam for general illuminance.
- UGR<22 as standard - UGR<19 optional
- Opal diffuser to provide homogenous lighting.
- Electrostatic powder painted durable metal body
- Monobloc poliuretano gasket to provide IP65 rating.
- Suitable for automation (DALI, 1-10V), human-centric (Tunable) lighting, emergency back-up battery

### Options:

- GST connector
- Security ceiling seismic suspension kit
- Various sizes and options to fit different ceilings




# Even-G 600 Recessed



Standard Colours




|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Optics</b>                | Opal PS diffuser                         |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant Current Pf>0.90                 |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |



| Item Code       | W  | Lm   | CCT  | CRI   | WxL     | Installation Dim. (mm) | Kg  |
|-----------------|----|------|------|-------|---------|------------------------|-----|
| 02142.66.30.033 | 28 | 3300 | 3000 | Ra>80 | 595x595 | 580x580                | 3,1 |
| 02142.66.30.036 | 33 | 3600 | 3000 | Ra>80 | 595x595 | 580x580                | 3,1 |
| 02142.66.40.034 | 28 | 3400 | 4000 | Ra>80 | 595x595 | 580x580                | 3,1 |
| 02142.66.40.037 | 33 | 3700 | 4000 | Ra>80 | 595x595 | 580x580                | 3,1 |




# Even-G 1200 Recessed



Standard Colours



|                              |  |
|------------------------------|--|
| <b>Body</b>                  | Electrostatic powder painted sheet steel |
| <b>Optics</b>                | Opal PS Diffuser                         |
| <b>Light Source</b>          | L80B20>50.000 hours SMD Mid Power LED    |
| <b>Driver</b>                | Constant current, Pf>0.90                |
| <b>Operating Voltage</b>     | 220-240V/50-60Hz                         |
| <b>Operating Temperature</b> | -20C°/+40C°                              |



| Item Code       | W  | Lm   | CCT  | CRI   | WxL      | Installation Dim (mm) | Kg  |
|-----------------|----|------|------|-------|----------|-----------------------|-----|
| 02142.31.30.032 | 33 | 3200 | 3000 | Ra>80 | 295x1195 | 280x1180              | 3,5 |
| 02142.31.30.040 | 52 | 4400 | 3000 | Ra>80 | 295x1195 | 280x1180              | 3,5 |
| 02142.31.40.033 | 33 | 3300 | 4000 | Ra>80 | 295x1195 | 280x1180              | 3,5 |
| 02142.31.40.041 | 52 | 4500 | 4000 | Ra>80 | 295x1195 | 280x1180              | 3,5 |

## İkizler Aydınlatma Armatürleri San. ve Tic. A.Ş.

### Merkez

**Adres** GİRNE MAH. İRMAKLAR SOK. KÜÇÜKYALI İŞ MERKEZİ  
F Blok No: 72/18 Maltepe / İSTANBUL  
Posta Kodu: 34852  
**Telefon** +90 (216) 397 22 16  
**Faks** +90 (216) 397 19 19

### Sakarya Fabrika

**Adres** 3. Organize San. Böl. 1. Yol. No: 68  
Soğucak Köyü SĞÜTLÜ/SAKARYA  
**Telefon** +90 (264) 290 40 10-11  
**Faks** +90 (264) 290 40 12

> [www.ikizlerlighting.com](http://www.ikizlerlighting.com) | E: [info@ikizlerlighting.com](mailto:info@ikizlerlighting.com)

  
"worth the light"